Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L10	2	("2731273").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/17 14:47
S1	241	(30/517).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 09:39
S2	199	(30/519).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 11:19
S3	428	(30/329).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 09:51
S4	454	(30/337).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 10:57
S5	621	(30/339).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 10:26
S6	158	(30/507).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 11:29
<b>S7</b>	175	(30/514).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 11:20
<b>S8</b>	557457	(collet socket)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:30
S9	2544496	(spring biasing near means)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:30
S10	2570922	(bolt pin)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:32
S11	145957	S8 and S9 and S10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:33

			•			
S12	14970	S8 with S9 with S10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:36
S13	62	S8 with S9 with S10 and (saw near3 blade)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:44
S14	1187116	blade saw cutter tool-head tool?head	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:45
S15	2180114	releasable exchange switching replacable interchangable	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:45
S16	108967	S15 and S14	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:46
S17	4911	S16 and S8 and S9 and S10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 11:47
S18	311	S16 and S8 with S9 with S10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 12:02
S19	18501	S16 and (cam cams camming)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON .	2006/02/15 12:03
S20	980	S19 and accentric acentric a?centric	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 12:05
S21	0	S15 same S14 with ((cam cams camming) with accentric)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 12:05

S22	4	"15" same "14" with ((cam cams camming) with accentric)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 13:27
S23	2	accentric adj groove	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 13:29
S24	3	accentric with groove with (locking retaining restraining)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 13:32
S25	11	interchangeable adj tool near4 blades	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/15 13:33
S26	91	(29/243).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 13:54
S27	74	(29/242).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/02/15 13:59
S28	2	tool adj head with fixer	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:51
S29	1667	tool near head with (fix\$3 affix\$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:52
S30	1546	tool near head with (fix\$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:52
S31	2545348	(spring biasing near means)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:53

			•			
S32	666	(tool near head with (fix\$3 )) and S31	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:54
S33	295	S32 and cam\$3	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 07:59
S34	74	spring near3 (BOLT PIN) with tool near head	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 08:12
S35	427	30/321.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 08:12
S36	140	279/2.14.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 13:32
S37	159	279/81.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 13:32
S38	344	279/71.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2006/02/16 13:56